

1/2 Pin" Cordless Impactool™, 1 057 Nm (780 lb-ft)



**Convenience of Cordless. Power of Air.**  
**The W7150EU-P High-Torque 1/2" Pin Impactool™ is the only cordless impact wrench that can perform as our best-in-class 2135PQXPA, 1/2" air Impactool. The W7150EU-P cordless tool will make quick work of tough jobs that professional technicians do every day. Do the Job! Do it Fast! Do it Every Time!**

- 1 057 Nm (780 ft-lb) of maximum torque and 1 486 Nm (1 100 ft-lb) of nut-busting torque, that's the best-in-class performance.
- All-metal impact mechanism and drive train provide the ultimate in durability and reliability.
- High-power rare earth magnet motor offers a long life and high power.
- Engineered composite housing for increased protection against chemical attack.
- Steel-reinforced housings add strength for unmatched drop resistance.
- Over-molded soft-touch grip minimizes vibration, reduces fatigue and enhances user comfort.
- Variable speed switch provides maximum control of the tool.
- Convenient one-hand operation with reverse control at trigger.
- High-capacity 5.0 Ah battery delivers maximum performance and runtime.
- Tool only is delivered without battery and charger. Kit K22 contains: cordless tool, charger, 2 pcs 20 V, 5.0 Ah Li-ion batteries and blow molded case.

## Specifications

Part Number	W7150EU-P
Ordering number (tool only)	47518087001
Part Number (kit Premium 5.0 Ah)	W7150EU-P-K22
Ordering number (kit Premium 5.0 Ah)	47518091001
Voltage (DC)	20 V
Drive size (square)	1/2 Pin in

## PERFORMANCE

Working torque in forward	50 - 550 ft-lb / 68 - 746 Nm
Maximum torque in forward	600 ft-lb / 813 Nm
Working torque in reverse	650 ft-lb / 880 Nm
Maximum torque in reverse	780 ft-lb / 1 057 Nm
Nut busting torque in reverse	1 100 ft-lb / 1 486 Nm
Free speed	0 - 1 900 rpm
Impacts per minute	2 300

## NOISE & VIBRATION

Sound pressure / power (EN60745)	89.0 / 100.0 dB(A)
Vibration level / measurement uncertainty (EN60745)	12.2 / 1.8 m/s <sup>2</sup>

## WEIGHT & DIMENSIONS

Tool weight with battery	6.8 lb / 3.1 kg
Tool dimensions with battery (L x W x H)	238 x 83 x 232 mm
Shipping weight (tool only)	6.2 lb / 2.8 kg
Shipping weight (kit)	16.7 lb / 7.6 kg
Shipping dimensions (tool only) (L x W x H)	229 x 267 x 92 mm
Shipping dimensions (kit) (L x W x H)	470 x 390 x 130 mm
UPC / EAN code (tool only)	6 63024 00999 4
UPC / EAN code (Kit 5.0 Ah)	6 63024 01010 5
Origin	Made in China





**SK4M5L**  
81287369  
1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



**SK4M18**  
81287385  
1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



**4UA9**  
03070216  
1/2" right-angle head  
(speed reduction: 25%  
torque output reduction: up to 50%)



**W7150-BOOT**  
48401855  
Protective tool boot



**BL2010**  
48386791  
Li-Ion battery, 20 V, 3.0 Ah



**BC1121-EU**  
47507874001  
Universal battery charger 12/20V



**67-4T**  
04637336  
Grease for high-speed angle heads



**SK4M14**  
81287351  
1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



**Impact sockets**  
For the complete range, see our accessory catalogue.



**W7000-CASE**  
48380976  
Carrying case



**BL2010-BOOT**  
47510964001  
Protective battery boot



**BL2022**  
47515902001  
Li-Ion battery, 20 V, 5.0 Ah



**L5110**  
48489561  
Task light (without battery)



**105-4T-6**  
04618930  
Grease for Impacttools hammer mechanism (6 tubes)